

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): An electron beam projection system comprising:
at least one process chamber, containing therein, at least one movable stage and at least one electric stage motor for moving the stage,
wherein the electrical stage motor includes magnetic coils encased in a coolant jacket which encloses the coils and encloses a coolant material,
wherein the coolant jacket includes coolant input lines for supplying coolant to the coolant jacket,
wherein the coolant jacket includes coolant return lines for allowing the coolant to flow out of the coolant jacket;
the process chamber including electrical leads for supplying electrical current to systems contained within the process chamber; and
wherein the electrical leads pass through the coolant return lines.

Claim 2 (original): An electron beam projection system as in Claim 1 wherein the at least one process chamber contains therein a vacuum environment.

Claim 3 (original): An electron beam projection system as in Claim 2 wherein the electrical leads include electrically insulated electrical leads.

Claim 4 (original): An electron beam projection system as in Claim 2 wherein the electrical leads are not electrically insulated; and
wherein the coolant contained in the coolant jacket consists of an electrically non-conductive coolant material.

Claim 11 (original): The electron beam projection system of Claim 10, wherein said electrically insulated electrical leads are spirally twisted together.

Claim 12 (original): The electron beam projection system of Claim 7 wherein the coolant comprises gas coolant.

Claim 13 (original): The electron beam projection system of Claim 7 wherein the coolant comprises liquid coolant.

Claim 14 (original): The electron beam projection system of Claim 13 wherein the liquid coolant comprises a non-conductive liquid coolant.

Claim 15 (original): The electron beam projection system of Claim 7, wherein coolant lines include pairs of coolant lines, each pair of coolant lines includes a first coolant output line and a second coolant output line and wherein said electrical leads comprise pairs of electrical leads arranged such that a first electrical lead of the pair of electrical leads is routed through the first coolant output line and such that such that a second electrical lead of the pair of electrical leads is routed through the second coolant output line.

Claim 16 (original): The electron beam projection system of Claim 15, wherein each pair of coolant lines is configured in a twisted arrangement, wherein the first coolant output line and the second coolant output line are twisted about each other so that the first electrical lead and the second electrical lead are arranged in a twisted pair arrangement.

Claim 17 (original): The electron beam projection system of Claim 7, wherein coolant lines include at least one coolant input line and at least one coolant output line and wherein said electrical leads are routed through the at least one coolant output line.

Claim 18 (original): The electron beam projection system of Claim 17, wherein the coolant comprises a non-conducting coolant material and wherein the electrical leads are not electrically insulated.

magnetic coils encased in a coolant jacket which encloses the coils and coolant and wherein coolant lines supply coolant to the coolant jacket and include coolant lines for passing coolant into the coolant jacket and at least one coolant return line enabling coolant efflux from the coolant jacket and wherein the process chamber includes electrical leads for supplying electrical current to systems contained within the process chamber, the method comprising:

flowing coolant through the coolant lines;

cooling the electrical leads by passing the electrical leads through the at least one coolant return line whereby the electrical leads are cooled by the coolant within the coolant return line
~~coolant lines whereby the electrical leads are cooled by the coolant.~~

Claim 26 (cancelled).

Claim 27 (currently amended): A method for cooling electrical leads as in Claim 25 ~~26~~ wherein the electrical leads for supplying electrical current to systems contained in the process chamber includes electrical leads for supplying electrical current to the stage motor and wherein cooling the electrical leads for supplying electrical current to the stage motor by passing the electrical leads through the at least one coolant return line whereby the electrical leads are cooled by the coolant.

Claim 28 (original): A method for cooling electrical leads as in Claim 27 wherein cooling the electrical leads by passing the electrical leads through the coolant lines for supplying coolant further comprises passing the electrical leads through a plurality of coolant return lines.

Claim 29 (new): An electron beam projection system comprising:
at least one process chamber containing therein a vacuum environment, and having therein, at least one movable stage and at least one electric stage motor for moving the stage,
wherein the electrical stage motor includes magnetic coils encased in a coolant jacket which encloses the coils and encloses an electrically non-conductive coolant material,
wherein the coolant jacket includes coolant input lines for supplying coolant to the coolant jacket,

wherein the coolant jacket includes coolant return lines for allowing the coolant to flow out of the coolant jacket;

the process chamber including un-insulated electrical leads for supplying electrical current to the at least one electric stage motor contained within the process chamber; and

wherein the electrical leads pass through the coolant lines.

Claim 30 (new): An electron beam projection system as in Claim 29 wherein the at least one movable stage includes a wafer stage for moving a semiconductor wafer during processing, and wherein the wafer stage includes an electrostatic chuck for securing the semiconductor wafer to the wafer stage, and wherein the electrical leads for supplying electrical current to systems further include electrical leads for supplying electrical power to the electrostatic chuck and wherein the electrical leads for supplying electrical power to the electrostatic chuck pass through the coolant lines.

Claim 31 (new): An electron beam projection system having a process chamber containing therein at least one movable stage and at least one electric stage motor for moving the stage;

wherein the stage motor includes magnetic coils encased in a coolant jacket which encloses the coils and coolant,

wherein coolant lines for supplying the coolant are connected to the coolant jacket, said coolant lines including pairs of coolant lines, wherein each pair of coolant lines includes a first coolant output line and a second coolant output line, and

wherein the stage motor includes pairs of electrical leads for supplying electrical current to the coils wherein said pairs of electrical leads are arranged such that a first electrical lead of the pair of electrical leads is routed through the first coolant output line and such that a second electrical lead of the pair of electrical leads is routed through the second coolant output line.

Claim 32 (new): The electron beam projection system of Claim 31, wherein each pair of coolant lines is configured in a twisted arrangement, wherein the first coolant output line and the second coolant output line are twisted about each other so that the first electrical lead and the second electrical lead are arranged in a twisted pair arrangement.

Claim 33 (new): The electron beam projection system of Claim 31 wherein the stage motor comprises a multi-phase linear stage motor.

Claim 34 (new): The electron beam projection system of Claim 31 wherein contains a vacuum processing environment.

Claim 35 (new): The electron beam projection system of Claim 31, wherein said electrical leads are electrically insulated.

Claim 36 (new): The electron beam projection system of Claim 31 wherein the coolant comprises gas coolant.

Claim 37 (new): The electron beam projection system of Claim 31 wherein the coolant comprises liquid coolant.

Claim 38 (new): The electron beam projection system of Claim 31, wherein the coolant comprises a non-conducting coolant material and wherein the electrical leads are not electrically insulated.